



尺寸：245×70×48mm

Features:

- Rated voltage mode power supply
- 180 ~ 264 VAC exchange input
- Small volume, light weight, high efficiency
- Protection characteristics: short circuit, overload, pressure, temperature
- Air cooling
- Meet the IP67 level
- 100% full load and machine test
- 2 years quality assurance

Electrical specifications

IP67 CE


Type		LPV-150-12	LPV-150-24	LPV-150-36
Output	Dc output voltage	12V	24V	36V
	Output voltage tolerance	±1%	±1%	±1%
	Rated output current	12.5A	6.3A	4.2A
	Output current range	0-12.5A	0-6.3A	0-4.2A
	Output power	150W	151W	151W
	Ripple and the noise	120mVp-p	120mVp-p	119mVp-p
	Start, up, and keep time	1000ms,30ms,24ms/230VAC		
Input	Input voltage range	180~264VAC 47~63Hz,255~373VDC		
	Exchange input current	1.8A/230VAC		
	Efficiency	82%	84%	85%
	Impulse current	Cold start current 40A/230VAC		
	Leakage current	<2.5mA/240VAC		
Protection characteristics	Overload protection	Rated output power of 105% ~ 135% start over load protection		
		Protection way: hiccups mode, load abnormal conditions can be removed to recover		
	Over-voltage protection	15~17V	30~32V	42~44V
		Protection way: hiccups mode, abnormal conditions can be removed to recover		
	Thermal protection	Shell temperature ≥85℃ , Start thermal protection		
		Protection way: cut output, the temperature is returning to normal after can be automatically restored		
Environment	Working temperature, humidity	-10℃~+60℃;20%~90%RH(Please refer to reduce the specified number load curve)		
	Keep temperature, humidity	-20℃~+85℃;10%~95%RH No condensation		
	Vibrate resistance	10~500Hz,2G 10min./1Cycle, duration 60 minutes, the axis		
Security	Compression sex	Input/output between: 1.5KVAC Input and ground: 1.5KVAC Output and ground: 0.5KVAC		
	Insulation resistance	Between input and output: input and the earth, the output and the earth: 100M Ohms/500VDC		
Conform to the standards	Safety standards	Accord with UL1012 IP67		
	EMC standards	Accord with EN55022,CLASSA		
Other	Weight	1.5kg 245*70*48mm (L*W*H)		
	Packaging	1.5kg/16pcs/25kg		

Note: 1. All the parameters in has not specified, all is in 230 VAC voltage input, rated load and 25 °C conditions measuring income value.

2. Ripple and noise voltage is in 20 MHz bandwidth oscilloscope take 12 inches double lines end with 0.1μ and 47μ when capacitance measurement.

3. Tolerance is voltage setting error, the voltage adjustment rate and the current adjust rate combined.

■ 机构尺寸 单位:mm




引出线分配表


输入端 (黑色三芯)		输出端 (白色二芯)	
棕色	AC/L	红色	DC OUTPUT +V
蓝色	AC/N	黑色	DC OUTPUT -V
黄绿	FG		

■ 原理图

频率: 65KHz



■ 负载减额曲线



■ 静态特性曲线

